



**Cubitron™ 3**  
Performance Abrasives



## Grinding & Cut-Off Wheels

Contact DGI Supply

1-800-923-6255

[www.dgisupply.com](http://www.dgisupply.com)

# Produce more. With less.

3M™ Cubitron™ 3 Grinding & Cut-Off Wheels feature 3M Precision-Shaped Ceramic Grain, which cuts faster and lasts longer than conventional grain. Designed for everyday high performance, helping you to reduce your manufacturing costs without compromising on performance.

A new era of heavy grinding and cutting:  
3M™ Cubitron™ 3  
Performance Abrasives.



Lasts longer



Cuts faster



Cuts cooler

# Our grinding & cut-off wheels have evolved.



Launched in 2012, this was the first range of cutting and grinding products using 3M's precision-shaped triangular grain abrasives. This range has now been replaced by our latest and best offering.



Significantly raising the benchmark for cut rate and product life in heavy grinding and cutting applications.

Up to  
**3X**  
Longer  
lasting

Responding to industry requirements for better product productivity, worker safety and sustainability, 3M has developed abrasive wheel technologies that make grinding & cut-off wheels work even faster and last even longer than our current best performing range. Performance is so good compared to existing 3M™ Cubitron™ II Performance Abrasives that we've established a new generation of products called 3M™ Cubitron™ 3 Performance Abrasives.

**Elevated  
experience**

To maximize simplicity and value to our customers, the current 3M™ Cubitron™ II Grinding & Cut-Off Wheel range will be discontinued and replaced by 3M™ Cubitron™ 3 Performance Abrasives. Customers will benefit from a wider product choice, better performance and optimized sustainability with no change in list price.

## Re-shaping the way work gets done.



### Our latest 3M Precision-Shaped Grain



We've re-engineered precision-shaped ceramic triangular grain using proprietary breakthroughs in **molecular bonding technology**.

### 3M Precision-Shaped Grain

3M pioneered the first precision-shaped grain using 3M microreplication technology to form consistent sharp peaks that easily "slice" through metal—cutting cooler, faster, and lasting longer than conventional abrasive grain.

### Conventional ceramic abrasive


Conventional ceramic abrasive grain tends to "plow" through metal, causing heat to build up in the workpiece and abrasive, resulting in a slower cut and shorter abrasive life compared to our latest precision-shaped grain.




# 3M™ Cubitron™ 3 Depressed Center Grinding Wheels




## 50% Longer life<sup>1</sup>




## 33% Less hand-arm vibration<sup>1</sup>



## 14% Faster cut<sup>1</sup>



## 43% Less noise<sup>1,2</sup>



Fast cutting, long lasting wheels that require less pressure for heavy grinding and weld removal.

### 3M™ Cubitron™ 3 Depressed Center Grinding Wheels

Part Number	3M ID	Type	Diameter (in)	Thickness (in)	Center Hole (in)
90001	7100303965	T27	4	1/4	3/8
88989	7100303964	T27	4	1/4	5/8
90003	7100303966	T27	4.5	1/4	7/8
90007	7100303967	T27	5	1/4	7/8
90005	7100313193	T27	6	1/4	7/8
90008	7100313198	T27	7	1/4	7/8
90010	7100313202	T27	9	1/4	7/8

#### Quick Change Attachment

90002	7100312968	T27	4.5	1/4	5/8-11
90004	7100312967	T27	5	1/4	5/8-11
90006	7100312966	T27	6	1/4	5/8-11
90009	7100312965	T27	7	1/4	5/8-11
90011	7100312964	T27	9	1/4	5/8-11

#### Single Packs

66203	7100317727	T27	4.5	1/4	7/8
66202	7100316886	T27 QC	4.5	1/4	5/8-11

1. Results are based on an automated beveling of 1018 carbon steel bars. Grinding wheel geometry is 115mm outer diameter mounted on a servo motor with an applied force of 12 lbs. Cut speed is defined by metal removed after 10 minutes of testing. The total material removal is estimated based on the amount of wheel used for 10 minutes of testing life. End of life is assumed to be 50% of the initial wheel mass.

2. Noise level operator exposure testing in a typical weld preparation process; 3M™ Cubitron™ 3 Depressed Center Grinding Wheels average compared to the average result of the high-quality ceramic bonded wheels tested, according to independent testing by Fraunhofer Institute, August 2023. Noise is measured in dB(A) and is a logarithmic number, a reduction of 3dB(A) is a halving of the noise intensity. Above 80dB(A) hearing protection should be provided. 105 decibels for high-quality grinding wheels, 102 decibels for 3M™ Cubitron™ 3 Depressed Center Grinding Wheels.

# 3M™ Cubitron™ 3 Cut-Off Wheels



Designed to provide high cut rates and long life to help reduce cost.




## Performance enhancing packaging

When cut-off wheels are properly protected from atmospheric moisture, product life can be extended.

All 3M™ Cubitron™ 3 Cut-Off Wheels will come in re-sealable, moisture resistant bags.


## 3X Longer life<sup>3</sup>



## 33% Less hand-arm vibration<sup>3</sup>



## 10% Faster cut<sup>3</sup>



3. Results are based on an automated cutting of a 3mm thick 304 stainless steel sheet. Cut-off wheel geometry is 125mm x 1.6mm x 22mm mounted on a 1.5 hp angle grinder with an applied force of 9 lbs. Cut speed is defined by time needed to cut 1 meter of stainless steel. The number of cuts is estimated by the amount of wheel that was used after cutting a distance of 1 meter. End of life is assumed to be 50% of initial wheel mass.


## 3M™ Cubitron™ 3 Cut-Off Wheels

Part Number	3M ID	Type	Diameter (in)	Thickness (mm)	Center Hole (in)
90030	7100303860	T1	3	0.035	1/4
90031	7100303859	T1	3	0.035	3/8
90032	7100303858	T1	3	0.06	3/8
90033	7100303857	T1	4	0.035	3/8
90034	7100304004	T1	4	0.045	3/8
90035	7100304005	T1	4	0.125	3/8
90051	7100304307	T1	4.5	0.04	7/8
90036	7100304006	T1	4.5	0.045	7/8
90037	7100304007	T1	5	0.045	7/8
90038	7100313190	T1	6	0.045	7/8
90039	7100313189	T1	7	0.09	7/8
90053	7100304308	T27	4.5	0.04	7/8
90041	7100304008	T27	4.5	0.045	7/8
90044	7100304009	T27	4.5	0.125	7/8
90045	7100304010	T27	5	0.045	7/8
90046	7100304011	T27	5	0.09	7/8
90044	7100304009	T27	5	0.125	7/8
90048	7100313201	T27	6	0.045	7/8
90050	7100313191	T27	7	0.09	7/8
Quick Change Attachment					
90043	7100313187	T27	4.5	0.125	5/8-11
90042	7100313200	T27	4.5	0.09	5/8-11
90040	7100313192	T27	4.5	0.045	5/8-11
90047	7100313188	T27	6	0.045	5/8-11
90049	7100312963	T27	7	0.09	5/8-11
Single Packs					
66199	7100317566	T27	4.5	0.045	7/8
66198	7100317466	T27	6	0.045	7/8

# 3M™ Cubitron™ 3 Cut & Grind Wheels



Versatile wheels are designed to be used as both a depressed center grinding wheel and as a cut-off wheel — making them ideal for cutting, grinding, gouging and more!



4. Results are based on an automated beveling of 1018 carbon steel bars. Cutting & grinding wheel geometry was 115mm outer diameter mounted on a servo motor with an applied force of 12 lbs. Cut speed is defined by metal removed after 10 minutes of testing. The total material removal is estimated based on the amount of wheel used for 10 minutes of testing life. End of life is assumed to be 50% of the initial wheel mass.

We've reformulated our Cut & Grind Wheel composition to offer:



**Smooth action**  
vs. 3M™ Cubitron™ II



**Best in class performance**




**Better balance**  
vs. 3M™ Cubitron™ II

### Range Expansion

Options for a thinner and faster cut:


- Current thickness (4.2mm) to be labeled as 5/32 in (previously labeled 1/8 in)
- Addition of a new thinner wheel (3.2mm) to be labeled as 1/8 in



### 3M™ Cubitron™ 3 Cut & Grind Wheels

Part Number	3M ID	Type	Diameter (in)	Thickness (in)	Center Hole (in)	
New!	89157	7100305149	T27 thin	4.5	1/8	7/8
New!	89160	7100305151	T27 thin	5	1/8	7/8
New!	89162	7100313586	T27 thin	6	1/8	7/8
New!	89163	7100313588	T27 thin	7	1/8	7/8
New!	89164	7100313759	T27 thin	9	1/8	7/8
	90012	7100305152	T27	4	5/32	3/8
	90014	7100303968	T27	4.5	5/32	7/8
	90018	7100305444	T27	5	5/32	7/8
	90019	7100313552	T27	6	5/32	7/8
	90021	7100313206	T27	7	5/32	7/8
	90023	7100313199	T27	9	5/32	7/8
Quick Change Attachment						
New!	89158	7100313760	T27 thin	4.5	1/8	5/8-11
New!	88990	7100313204	T27 thin	5	1/8	5/8-11
New!	88991	7100313205	T27 thin	6	1/8	5/8-11
New!	88992	7100313195	T27 thin	7	1/8	5/8-11
New!	88993	7100313197	T27 thin	9	1/8	5/8-11
	90016	7100313194	T27	4.5	5/32	5/8-11
	90017	7100313550	T27	5	5/32	5/8-11
	90020	7100313196	T27	6	5/32	5/8-11
	90022	7100313551	T27	7	5/32	5/8-11
	90024	7100313203	T27	9	5/32	5/8-11
Single Packs — Quick Change Attachment						
New!	66200	7100316747	T27	6	5/32	5/8-11
New!	66201	7100317773	T27 thin	6	1/8	5/8-11

# 3M™ Grinding and Cut-Off Wheel product performance comparisons



Attributes	Aluminum oxide	Alumina zirconia	3M™ Silver	3M™ Cubitron™ 3
Durability / life	★★	★★★	★★★★★	★★★★★
Speed of cut	★	★★	★★★	★★★★★
Feel: smooth	★★	★★★	★★★★★	★★★★★
Contaminant-free* (for stainless/inox)	varies	varies	yes	yes
Mineral	aluminum oxide	alumina zirconia	blend of precision-shaped ceramic grain	precision-shaped ceramic grain
Abrasive cost per job	\$\$\$	\$\$	\$	\$\$
Total cost of job (abrasive, labor, processes)	\$\$\$\$	\$\$\$	\$\$	\$

\*Contains less than 0.1% Fe, S and Cl.

## 3M™ Silver and Advanced Series

### 3M™ Cut and Grind Wheels

UPC (638060-)	Type	Diameter×Center Hole (in)	Max RPM	Max Speed (m/s)	Box/Case
06459-7	T1	4 × 1/8 × 3/8	15,300	80	10/20
06460-3	T27	4 × 1/8 × 3/8	15,300	80	10/20
06461-0	T27	4 × 1/8 × 5/8	15,300	80	10/20
06462-7	T27	4-1/2 × 1/8 × 7/8	13,300	80	10/20
06463-4	T27	5 × 1/8 × 7/8	12,500	80	10/20
06469-6	T27	6 × 1/8 × 7/8	10,200	80	10/20
06470-2	T27	7 × 1/8 × 7/8	8,500	80	10/20
06471-9	T27	9 × 1/8 × 7/8	6,650	80	10/20
Quick Change Attachment					
06464-1	T27	4-1/2 × 1/8 × 5/8-11	13,300	80	10/20
06465-8	T27	5 × 1/8 × 5/8-11	12,500	80	10/20
06466-5	T27	6 × 1/8 × 5/8-11	10,200	80	10/20
06467-2	T27	7 × 1/8 × 5/8-11	8,500	80	10/20
06468-9	T27	9 × 1/8 × 5/8-11	6,650	80	10/20

### 3M™ Silver Depressed Center Grinding Wheel

UPC (051125-)	Type	Diameter×Thickness × Arbor Hole (in)	Max RPM	Box/Case
87455-7	T27	4 × 1/4 × 3/8	15,300	10/20
87456-4	T27	4 × 1/4 × 5/8	15,300	10/20
87453-3	T27	4-1/2 × 1/4 × 7/8	13,300	10/20
87454-0	T27	5 × 1/4 × 7/8	12,250	10/20
87450-2	T27	6 × 1/4 × 7/8	10,200	10/20
87451-9	T27	7 × 1/4 × 7/8	8,500	10/20
87452-6	T27	9 × 1/4 × 7/8	6,650	10/20
Quick Change Attachment				
87397-0	T27	4-1/2 × 1/4 × 5/8-11	13,300	10/20
87446-5	T27	5 × 1/4 × 5/8-11	12,250	10/20
87447-2	T27	6 × 1/4 × 5/8-11	10,200	10/20
87448-9	T27	7 × 1/4 × 5/8-11	8,500	10/20
87449-6	T27	9 × 1/4 × 5/8-11	6,650	10/20

### 3M™ Silver Cut-Off Wheels

UPC (051125-)	Type	Diameter×Thickness × Arbor Hole (in)	Max RPM	Box/Case
87457-1	T1	3 × 0.035 × 1/4	25,465	25/50
87458-8	T1	3 × 0.035 × 3/8	25,465	25/50
87459-5	T1	3 × 0.060 × 3/8	25,465	25/50
87460-1	T1	4 × 0.035 × 1/4	19,100	25/50
87461-8	T1	4 × 0.035 × 3/8	19,100	25/50
87462-5	T1	4 × 0.060 × 3/8	19,100	25/50
87657-5	T1	4 × 0.125 × 3/8	19,100	25/50
87464-9	T1	4.5 × 0.040 × 7/8	13,300	25/50
87465-6	T1	4.5 × 0.045 × 7/8	13,300	25/50
87467-0	T1	5 × 0.045 × 7/8	12,250	25/50
87469-4	T1	6 × 0.045 × 7/8	10,200	25/50
87471-7	T1	7 × 0.045 × 7/8	8,500	25/50
87466-3	T27	4.5 × 0.045 × 7/8	13,300	25/50
87659-9	T27	4.5 × 0.093 × 7/8	13,300	25/50
87468-7	T27	5 × 0.045 × 7/8	12,250	10/20
87470-0	T27	6 × 0.045 × 7/8	10,200	10/20



3M has you covered when it comes to grinding and cutting. Offering a wide range of options tailored to your unique needs.

# Tools that take it to the next level.

The new 3M™ Pneumatic Angle Grinders is a powerful tool that features superior performance and world-class ergonomic design. Built with robust components for durability and reliability in the harshest industrial conditions.

- 1.5HP (1100W power)
- Wheel autobalancer
- Spindle lock
- Vibration-reducing side handle with added padding—interchangeable for right or left hand usage
- Available accessories provide maximum functionality and flexibility
- Rear exhaust directs exhaust and swarf away from the workpiece
- Adjustable guard



## 3M™ Pneumatic Angle Grinder

UPC (638060-)	Diameter (in)	Motor HP (W)	Max RPM	Box/Case
88566-6	5	1.5 (1100)	12,000	1/1



## TECH TIPS

### Powering up for performance

- Portable bonded products perform better the faster they run, so having a tool able to maintain speed is crucial
- The higher the tool power, the easier it can maintain speed, resulting in faster cut time and longer wheel life
- When the tool speed decreases, wheel wear typically increases
- **Do not** exceed the maximum operating speed listed on the wheel!
- Always use a tool guard

Industries: Metal fabrication ▶ Machinery manufacturing ▶ Shipyards



Ideal for applications: Beveling ▶ Cutting ▶ Weld grinding



## Sustainability matters to 3M Abrasives.

When you buy from the SEAM value chain, you are helping to build a sustainable future for our industry, for people and for the planet.

3M is a founding member of the SEAM abrasives manufacturers program and aligns to the world's highest standards of quality, safety and performance in a sustainable environment. We commit to transparency, accountability, innovation and progress.

When buying from the SEAM value chain, customers are helping to build themselves a sustainable future.



Sustainable European Abrasive Manufacturers

Find out more at  
[www.seam.earth](http://www.seam.earth)



Learn more at [3M.com/Cubitron3](http://3M.com/Cubitron3)



**3M Abrasive Systems**  
**3M Center, Building 223-6N-02**  
**St. Paul, MN 55144 USA**

Phone 1-866-279-1235  
Web [3M.com/abrasives](http://3M.com/abrasives)

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. **Disclaimer:** 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and other limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, death, or property damage. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit [www.3M.com](http://www.3M.com). **Warranty and Limited Remedy:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M and Cubitron are trademarks of 3M Company. All other trademarks are property of their respective owners. © 3M 2023. All rights reserved. 61-5005-0083-2

**3M Abrasive Products are for industrial use only.**

