



100 Lakeview Parkway, Vernon Hills, Illinois 60061

DGI
SUPPLY®



SAWING PRODUCTS

SOLUTIONS FOR ALL YOUR SAWING NEEDS!

Looking for a practical and cost - effective machine to fulfill your sawing requirements?

DS-280M is the best design for your fabrication needs.

DS-280M

**IN STOCK
SHOP NOW!**



<https://bit.ly/3XsKihL>



**NEED AN ADDITIONAL SAW BLADE?
Try DoALL® Silencer™ Plus**

SHOP NOW!



https://bit.ly/DoALL_Silencer_Blade

** FOB SHIPPING POINT

**CONTACT US TODAY TO LEARN MORE
1-800-923-6255 | www.dgisupply.com**

PURCHASE INCLUDES!

ACCESSORIES INCLUDED HELPING YOUR FABRICATION SHOP PERFORM DAILY CUTTING PROJECTS WITH EASE AND MINIMAL SPACE!

- ✓ Dual swivel head to 45 left to 60 degrees right
- ✓ Fine adjustment head feed control
- ✓ Push button control panel
- ✓ Carbide faced saw guide inserts
- ✓ 3 ft manual set work stop
- ✓ Blade driven cleaning brush
- ✓ Two speed band motor
- ✓ Counter balance springs
- ✓ Manual band tension
- ✓ Recirculating coolant system
- ✓ Movable two position vise system
- ✓ Saw blade guards
- ✓ Band door interlocks
- ✓ Operation and parts manuals on USB stick
- ✓ One (1) complimentary DoALL Bi Metal saw blade
- ✓ Complimentary DoALL Cutting Fluids package

MACHINE DETAILS & SPECS

Easy to operate, ergonomically placed push-button control panel, along with quick release clamp/unclamp vice handle gives the machine the opportunity to create quick single and small production run pieces. The saw head feed is controlled by use of the balanced head weight assisted by a micrometer adjusted hydraulic valve. The two band speeds allow for the cutting of different material types by use of a 1-1.5 hp electric motor. Miter cuts from 45 degrees left to 60 degrees right are able to be made by manually unlocking and adjusting the head to the desired position via an on board protractor.

Machine specs:

- ✓ Saw Blade - Width x Length - 1" x 107"
- ✓ Motor HP - 1-1.5
- ✓ Band Speed - 115-230 fpm
- ✓ Band Tension - Manual
- ✓ Coolant System – Flood

Floor Space Dimensions:

- ✓ W x L X H - 64" x 35" x 74"
- ✓ Material Pass Height 31.5"
- ✓ Machine Weight 618 lbs.

Electrical:

- ✓ Voltage Requirement 230V-60Hz-3ph, Wye configuration
- ✓ Total Amp Draw (FLA) 8 Amps



CONTACT US TODAY TO LEARN MORE
1-800-923-6255 | www.dgisupply.com

LET US HELP WITH THE HEAVY LIFTING!



ENDLESS ROUND SLINGS THE RIGHT SLING FOR YOUR NEXT LIFT



The Tuflex® difference is easy to see. The cost-saving, capacity, and strength these roundslings offer is like no other sling.

- Wear points can be shifted to extend sling life.
- The most flexible style of sling.
- Individual slings can be attached together using appropriate hardware.
- WLL (working load limit) up to 200,000 lbs.



ADJUST-A-LINK GRADE 100 CHAIN SLINGS

Adjust-A-Link is versatile and easily adjusts to accommodate a wide range of applications. From helping lift a new band saw into place or to load material on to the saw itself, the Adjust-A-Link reduces the need for multiple slings of different lengths and configurations. It's designed with patented alloy steel master control link for strength and reliability.

OSHA compliant.



CONTACT US TODAY TO LEARN MORE
1-800-923-6255 | www.dgisupply.com

HAVE YOU DONE A SLING INSPECTION THIS YEAR?



Did you know?

OSHA regulations require that all chain slings receive a thorough inspection at least once per year by a competent person.



Contact DGI
Supply for a FREE
inspection



CONTACT US TODAY TO SCHEDULE YOUR SLING INSPECTION
1-800-923-6255 | www.dgisupply.com