

SHARP CURRENTLY HAS 225 MACHINES IN STOCK FOR IMMEDIATE DELIVERY, INCLUDING:

- Manual & CNC Knee Milling Machines
- Horizontal Knee Mills
- Vertical/Knee Mill Combinations
- Vertical Bed Mills
- Horizontal Boring Mills
- Ultra-High Precision Tool Room Lathes
- Variable Speed & Head Engine Lathes
- CNC Precision Flat Bed Lathes
- Surface Grinders
- Manual, NC, and CNC OD Grinders
- Radial Arm Drills
- 3 Axis VMC's
- 5 Axis VMC's

SHARP FEATURED PRODUCTS OF THE MONTH LATHES & GRINDERS

LATHES



GRINDERS



SHARP

MACHINES FOR THE WHOLE SHOP.
ALL IN ONE LOCATION.

**IN STOCK FOR
IMMEDIATE DELIVERY!**

SHARP LATHES TURNING PROFITS



1340VS
VIDEO

MANUAL PRECISION LATHE

1340VS-K Premium Package

- Newall NMS 300, 2-axis DRO
- Chuck guard with limit switch
- 13" Swing 40" Between Centers
- 3 HP motor
- Digital Variable Speed (DVS) (40-2,000 rpm)
- Cross slide movement control at apron
- D1-4 Camlock spindle 1 1/2" bore
- Gap Bed
- Hardened and ground chrome-moly gears
- Halogen Work Light



1118H
VIDEO

MANUAL PRECISION LATHE

1118H

- 11" Swing 18" Between Centers
- 5 HP Motor Digital Variable Speed Drive (infinitely variable 130-4,000 rpm)
- Spindle Accuracy TIR 0.000050 in
- 5C Collet Closer
- Independent electric feed-rate control on carriage and cross slide.
- Quick-action compound slide for threading.
 - Inch threads (36) 11-108
 - Metric threads (36) 0.275-2.7

SHARP

MACHINES FOR THE WHOLE SHOP.
ALL IN ONE LOCATION.

**IN STOCK FOR
IMMEDIATE DELIVERY!**

SHARP GRINDERS FOR TIGHT TOLERANCE PARTS



**SG-618
VIDEO**

MANUAL SURFACE GRINDER

SG-618

- Table Size 6x18"
- 6x18" Kanetsu Permanent Magnetic Chuck
- 1.5 HP motor
- TURCITE ways for oil retention
- Smooth wire-rope driven table
- Hardened and ground lead screw
- One "V", one flat way longitudinal travel
- Double "V" way cross travel
- Both ways are hand scraped and covered with TURCITE B coating



**OD-820 SE
VIDEO**

AUTOMATIC OD/ID GRINDER

OD-820 SE

- NC wheel head infeed with servo drive and ball screw
- Touch screen operation panel with conversational type data input
- 8" max diameter, 20" length
- 3 HP motor
- Auto table feed
- 14" x 1.5" x 5" wheel
- Work head spindle runout 0.000050" TIR
- Spindle, wheel head & work head have var. spd. drv.
- Table can swivel for taper grinding